Superior PCs
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO E9900 E-Star 5.0
	Your desktop without compromises
Operating system* preinstalled	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts Mainboard	D2924 (proprietary)
Chipset	Intel® Q57
Processor Type, Second Level cache, Processor frequency	Intel® Core™ i7-870 processor, 8 MB, 2.93 GHz Intel® Core™ i5-760 processor, 8 MB, 2.80 GHz Intel® Core™ i5-680 processor, 4 MB, 3.60 GHz Intel® Core™ i5-660 processor, 4 MB, 3.33 GHz Intel® Core™ i5-650 processor, 4 MB, 3.20 GHz Intel® Core™ i3-550 processor, 4 MB, 3.20 GHz Intel® Pentium® processor G6950, 3 MB, 2.80 GHz
Memory	Up to 16 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
Drives (optional)	DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I MultiCard Reader 20-in-1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x 16 1 x PCI-Express x8 (mech. x16) LP 2 x PCI slots LP or 1 x PCI-Express 2.0 x16 LP 2 x PCI slots FH
Interfaces	1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal 1 x VGA (via DVI to VGA adapter; included for onboard graphics only) 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 x Parallel (25pin with EPP and ECP) (optional) 1 x Ethernet (RJ-45) 1 x DVI (for onboard graphics only) 1 x DisplayPort (for onboard graphics only) 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics (integrated in dual-core processors only), up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Intel® 82578 DM
Dimensions (W x D x H)	340 x 380 x 100 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 84% / 87% / 85%
Special features	Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, up to 87 % energy efficient power supply, Blue Angel certified, Family Concept, Embedded Security (TPM)
Standard Warranty Duration**	3 years (depending on country)
Service level**	Bring-In / On-Site Service (depending on country)

Superior PCs
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO E9900 0-Watt
	The innovative 0-Watt PC
Operating system* preinstalled	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts Mainboard	D2924 (proprietary)
Chipset	Intel® Q57
Processor Type, Second Level cache, Processor frequency	Intel® Core™ i7-870 processor, 8 MB, 2.93 GHz Intel® Core™ i5-760 processor, 8 MB, 2.80 GHz Intel® Core™ i5-680 processor, 4 MB, 3.60 GHz Intel® Core™ i5-660 processor, 4 MB, 3.33 GHz Intel® Core™ i5-650 processor, 4 MB, 3.20 GHz Intel® Core™ i3-550 processor, 4 MB, 3.20 GHz Intel® Pentium® processor G6950, 3 MB, 2.80 GHz
Memory	Up to 16 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
Drives (optional)	DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I MultiCard Reader 20-in-1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x 16 1 x PCI-Express x8 (mech. x16) LP 2 x PCI slots LP or 1 x PCI-Express 2.0 x16 LP 2 x PCI slots FH
Interfaces	1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal 1 x VGA (via DVI to VGA adapter; included for onboard graphics only) 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 x Parallel (25pin with EPP and ECP) (optional) 1 x Ethernet (RJ-45) 1 x DVI (for onboard graphics only) 1 x DisplayPort (for onboard graphics only) 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics (integrated in dual-core processors only), up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Intel® 82578 DM
Dimensions (W x D x H)	340 x 380 x 100 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 86% / 89% / 87%
Special features	0-Watt in off- / hibernating mode, Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, 89 % energy efficient power supply, Blue Angel certified, Switched monitor outlet, Family Concept, Embedded Security (TPM)
Standard Warranty Duration**	3 years (depending on country)
Service level**	Bring-In / On-Site Service (depending on country)

Superior PCs
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO P9900 E-Star 5.0	ESPRIMO P9900 0-Watt
	The expandable business workhorse	The innovative 0-Watt PC
Operating system* preinstalled	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts Mainboard	D2912 (µBTX)	D2912 (µBTX)
Chipset	Intel® Q57	Intel® Q57
Processor Type, Second Level cache, Processor frequency	Intel® Core™ i7-870 processor, 8 MB, 2.93 GHz Intel® Core™ i5-760 processor, 8 MB, 2.80 GHz Intel® Core™ i5-680 processor, 4 MB, 3.60 GHz Intel® Core™ i5-660 processor, 4 MB, 3.33 GHz Intel® Core™ i5-650 processor, 4 MB, 3.20 GHz Intel® Core™ i3-550 processor, 4 MB, 3.20 GHz Intel® Pentium® processor G6950, 3 MB, 2.80 GHz	Intel® Core™ i7-870 processor, 8 MB, 2.93 GHz Intel® Core™ i5-760 processor, 8 MB, 2.80 GHz Intel® Core™ i5-680 processor, 4 MB, 3.60 GHz Intel® Core™ i5-660 processor, 4 MB, 3.33 GHz Intel® Core™ i5-650 processor, 4 MB, 3.20 GHz Intel® Core™ i3-550 processor, 4 MB, 3.20 GHz Intel® Pentium® processor G6950, 3 MB, 2.80 GHz
Memory	Up to 16 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).	Up to 16 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.
Serial ATA	4	4
thereof eSATA	2 (optional)	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
Drives (optional)	DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I MultiCard Reader 20-in-1, 3.5-inch, USB 2.0	DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I MultiCard Reader 20-in-1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16; 1 x PCI-Express x8 (mech. x16); 2 x PCI slots	1 x PCI-Express 2.0 x16; 1 x PCI-Express x8 (mech. x16); 2 x PCI slots
Interfaces	1 x Audio: line-in / microphone; 1 x Audio: line-in; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; 14 x USB 2.0 total; 2 x USB front; 8 x USB rear; 4 x USB internal; 1 x VGA (via DVI to VGA adapter; included for onboard graphics only); 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible); 1 x Parallel (25pin with EPP and ECP) (optional); 1 x Ethernet (RJ-45); 1 x DVI (for onboard graphics only); 1 x DisplayPort (for onboard graphics only); 2 x Mouse / Keyboard (PS/2)	1 x Audio: line-in / microphone; 1 x Audio: line-in; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; 14 x USB 2.0 total; 2 x USB front; 8 x USB rear; 4 x USB internal; 1 x VGA (via DVI to VGA adapter; included for onboard graphics only); 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible); 1 x Parallel (25pin with EPP and ECP) (optional); 1 x Ethernet (RJ-45); 1 x DVI (for onboard graphics only); 1 x DisplayPort (for onboard graphics only); 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics (integrated in dual-core processors only), up to 1759 MB	Intel® HD Graphics (integrated in dual-core processors only), up to 1759 MB
Audio codec	Realtek ALC663	Realtek ALC663
LAN	10/100/1000 Mbit/s Intel® 82578 DM	10/100/1000 Mbit/s Intel® 82578 DM
Dimensions (W x D x H)	203 x 390 x 392 mm	203 x 390 x 392 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 85% / 87% / 85%	Power supply efficiency (at 230V; 20% / 50% / 100% load): 86% / 89% / 87%
Special features	Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, up to 87 % energy efficient power supply, Blue Angel certified, Family Concept, Embedded Security (TPM)	0-Watt in off- / hibernating mode, Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, 89 % energy efficient power supply, Blue Angel certified, Switched monitor outlet, Family Concept, Embedded Security (TPM)
Standard Warranty Duration**	3 years (depending on country)	3 years (depending on country)
Service level**	Bring-In / On-Site Service (depending on country)	Bring-In / On-Site Service (depending on country)

Superior PCs
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO Q9000
	The mini with more PC per cm³
Operating system* preinstalled	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Chipset	Intel® QM57
Processor Type, Second Level cache, Processor frequency	Intel® Core™ i5-560M processor, 3 MB, 2.66 GHz Intel® Core™ i3-370M processor, 3 MB, 2.40 GHz Intel® Celeron® processor P4600, 2 MB, 2.00 GHz
Memory	Up to 4 GB, 2 SO DIMM slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. In configurations with 4 GB the visible memory may be reduced to approximately 3.5 GB or less (for 32 bit operating systems, depending on system configuration)
Serial ATA	3
Controller functions	Serial ATA II, 3 Gbit, AHCI
Drives (optional)	Blu-ray Combo SATA Slot-in slim, SATA DVD Super Multi Slot-in slim, SATA
Hard disk drive	SATA, 5400 rpm, 160 GB, 2.5-inch SATA, 5400 rpm, 250 GB, 2.5-inch SATA II, 5400 rpm, 320 GB, 2.5-inch SATA II, 5400 rpm, 500 GB, 2.5-inch SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
Drive bays	1 x 2.5-inch bay 1 x 5.25-inch external bay
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out / headphones / SPDIF (optical) 6 x USB 2.0 total 2 x USB front 4 x USB rear 1 x VGA (via DVI to VGA-Adapter) 1 x Ethernet (RJ-45) 1 x DVI 1 x eSATA 1 x HDMI
Graphics	Intel® HD Graphics
Audio codec	Realtek ALC662
LAN	10/100/1000 Mbit/s Intel® 82577 LM 1 (optional) x Integrated WLAN
Dimensions (W x D x H)	165 x 168 x 57 mm
Communication	Bluetooth (optional) WLAN (optional)
Special features	ENERGY STAR® 5.0, Mobile on Desktop, Backpack Solution, Extremely space-saving design, Intel® vPro™ technology, Blue Angel certified, Embedded Security (TPM)
Standard Warranty Duration**	3 years (depending on country)
Service level**	Bring-In / On-Site Service (depending on country)

	ESPRIMO E7936 E85+
	Your desktop without compromises
Operating system* preinstalled	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts Mainboard	D3028 (proprietary)
Chipset	Intel® Q45
Processor Type, Second Level cache, Processor frequency	Intel® Core™2 Quad processor Q9650, 12 MB, 3.00 GHz Intel® Core™2 Quad processor Q9550, 12 MB, 2.83 GHz Intel® Core™2 Quad processor Q9505, 6 MB, 2.83 GHz Intel® Core™2 Quad processor Q8300, 4 MB, 2.50 GHz Intel® Core™2 Duo processor E8600, 6 MB, 3.33 GHz Intel® Core™2 Duo processor E8500, 6 MB, 3.16 GHz Intel® Core™2 Duo processor E8400, 6 MB, 3.00 GHz Intel® Core™2 Duo processor E7600, 3 MB, 3.06 GHz Intel® Core™2 Duo processor E7500, 3 MB, 2.93 GHz Intel® Pentium® processor E6600, 2 MB, 3.06 GHz Intel® Pentium® processor E5700, 2 MB, 3.00 GHz Intel® Pentium® processor E5400, 2 MB, 2.70 GHz Intel® Celeron® processor 450, 512 KB, 2.20 GHz
Memory	Up to 16 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I MultiCard Reader 20-in-1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 LP 1 x PCI-Express x4 (mech. x8) LP 2 x PCI slots LP or 1 x PCI-Express 2.0 x 16 LP 2 x PCI Full High
Interfaces	1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal 1 x VGA 2 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 x Parallel (25pin with EPP and ECP) (optional) 1 x Ethernet (RJ-45) 1 x DVI (optional) 1 x DisplayPort (optional) 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Intel® 82567 LM
Dimensions (W x D x H)	340 x 380 x 100 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 84% / 87% / 85%
Special features	Intel® vPro™ technology, Green PC, up to 87 % energy efficient power supply, Family Concept, Embedded Security (TPM)
Standard Warranty Duration**	3 years (depending on country)
Service level**	Bring-In / On-Site Service (depending on country)

Superior PCs
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO E7936 E-Star 5.0
	Your desktop without compromises
Operating system* preinstalled	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts Mainboard	D3028 (proprietary)
Chipset	Intel® Q45
Processor Type, Second Level cache, Processor frequency	Intel® Core™2 Quad processor Q9650, 12 MB, 3.00 GHz Intel® Core™2 Quad processor Q9550, 12 MB, 2.83 GHz Intel® Core™2 Quad processor Q9505, 6 MB, 2.83 GHz Intel® Core™2 Quad processor Q8300, 4 MB, 2.50 GHz Intel® Core™2 Duo processor E8600, 6 MB, 3.33 GHz Intel® Core™2 Duo processor E8500, 6 MB, 3.16 GHz Intel® Core™2 Duo processor E8400, 6 MB, 3.00 GHz Intel® Core™2 Duo processor E7600, 3 MB, 3.06 GHz Intel® Core™2 Duo processor E7500, 3 MB, 2.93 GHz Intel® Pentium® processor E6600, 2 MB, 3.06 GHz Intel® Pentium® processor E5700, 2 MB, 3.00 GHz Intel® Celeron® processor E3400, 1 MB, 2.60 GHz
Memory	Up to 16 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I MultiCard Reader 20-in-1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 LP 1 x PCI-Express x4 (mech. x8) LP 2 x PCI slots LP or 1 x PCI-Express 2.0 x 16 LP 2 x PCI Full High
Interfaces	1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal 1 x VGA 2 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 x Parallel (25pin with EPP and ECP) (optional) 1 x Ethernet (RJ-45) 1 x DVI (optional) 1 x DisplayPort (optional) 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Intel® 82567 LM
Dimensions (W x D x H)	340 x 380 x 100 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 84% / 87% / 85%
Special features	Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, up to 87 % energy efficient power supply, Blue Angel certified, Family Concept, Embedded Security (TPM)
Standard Warranty Duration**	3 years (depending on country)
Service level**	Bring-In / On-Site Service (depending on country)

Superior PCs
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO E7936 0-Watt
	The innovative 0-Watt PC
Operating system* preinstalled	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts Mainboard	D3028 (proprietary)
Chipset	Intel® Q45
Processor Type, Second Level cache, Processor frequency	Intel® Core™2 Quad processor Q9650, 12 MB, 3.00 GHz Intel® Core™2 Quad processor Q9550, 12 MB, 2.83 GHz Intel® Core™2 Quad processor Q9505, 6 MB, 2.83 GHz Intel® Core™2 Quad processor Q8300, 4 MB, 2.50 GHz Intel® Core™2 Duo processor E8600, 6 MB, 3.33 GHz Intel® Core™2 Duo processor E8500, 6 MB, 3.16 GHz Intel® Core™2 Duo processor E8400, 6 MB, 3.00 GHz Intel® Core™2 Duo processor E7600, 3 MB, 3.06 GHz Intel® Core™2 Duo processor E7500, 3 MB, 2.93 GHz Intel® Pentium® processor E6600, 2 MB, 3.06 GHz Intel® Pentium® processor E5700, 2 MB, 3.00 GHz Intel® Celeron® processor E3400, 1 MB, 2.60 GHz
Memory	Up to 16 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I MultiCard Reader 20-in-1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 LP 1 x PCI-Express x4 (mech. x8) LP 2 x PCI slots LP or 1 x PCI-Express 2.0 x 16 LP 2 x PCI Full High
Interfaces	1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal 1 x VGA 2 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 x Parallel (25pin with EPP and ECP) (optional) 1 x Ethernet (RJ-45) 1 x DVI (optional) 1 x DisplayPort (optional) 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Intel® 82567 LM
Dimensions (W x D x H)	340 x 380 x 100 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 86% / 89% / 87%
Special features	0-Watt in off- / hibernating mode, Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, 89 % energy efficient power supply, Blue Angel certified, Switched monitor outlet, Family Concept, Embedded Security (TPM)
Standard Warranty Duration**	3 years (depending on country)
Service level**	Bring-In / On-Site Service (depending on country)

Superior PCs
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO P7936 E85+
	The expandable business workhorse
Operating system* preinstalled	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts Mainboard	D3012 (µBTX)
Chipset	Intel® Q45
Processor Type, Second Level cache, Processor frequency	Intel® Core™2 Quad processor Q9650, 12 MB, 3.00 GHz Intel® Core™2 Quad processor Q9550, 12 MB, 2.83 GHz Intel® Core™2 Quad processor Q9505, 6 MB, 2.83 GHz Intel® Core™2 Quad processor Q8300, 4 MB, 2.50 GHz Intel® Core™2 Duo processor E8600, 6 MB, 3.33 GHz Intel® Core™2 Duo processor E8500, 6 MB, 3.16 GHz Intel® Core™2 Duo processor E8400, 6 MB, 3.00 GHz Intel® Core™2 Duo processor E7600, 3 MB, 3.06 GHz Intel® Core™2 Duo processor E7500, 3 MB, 2.93 GHz Intel® Pentium® processor E6600, 2 MB, 3.06 GHz Intel® Pentium® processor E5700, 2 MB, 3.00 GHz Intel® Celeron® processor E3400, 1 MB, 2.60 GHz Intel® Celeron® processor 450, 512 KB, 2.20 GHz
Memory	Up to 16 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I MultiCard Reader 20-in-1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 1 x PCI-Express x4 (mech. x8) 2 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal, thereof 2 optional rear 1 x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 x Parallel (25pin with EPP and ECP) (optional) 1 x Ethernet (RJ-45) 1 x DVI (optional) 1 x DisplayPort (optional) 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Intel® 82567 LM
Dimensions (W x D x H)	203 x 390 x 392 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 85% / 87% / 85%
Special features	Intel® vPro™ technology, Green PC, up to 87 % energy efficient power supply, Family Concept, Embedded Security (TPM)
Standard Warranty Duration**	3 years (depending on country)
Service level**	Bring-In / On-Site Service (depending on country)

Superior PCs
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO P7936 E-Star 5.0
	The expandable business workhorse
Operating system* preinstalled	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts Mainboard	D3012 (µBTX)
Chipset	Intel® Q45
Processor Type, Second Level cache, Processor frequency	Intel® Core™2 Quad processor Q9650, 12 MB, 3.00 GHz Intel® Core™2 Quad processor Q9550, 12 MB, 2.83 GHz Intel® Core™2 Quad processor Q9505, 6 MB, 2.83 GHz Intel® Core™2 Quad processor Q8300, 4 MB, 2.50 GHz Intel® Core™2 Duo processor E8600, 6 MB, 3.33 GHz Intel® Core™2 Duo processor E8500, 6 MB, 3.16 GHz Intel® Core™2 Duo processor E8400, 6 MB, 3.00 GHz Intel® Core™2 Duo processor E7600, 3 MB, 3.06 GHz Intel® Core™2 Duo processor E7500, 3 MB, 2.93 GHz Intel® Pentium® processor E6600, 2 MB, 3.06 GHz Intel® Pentium® processor E5700, 2 MB, 3.00 GHz Intel® Celeron® processor E3400, 1 MB, 2.60 GHz
Memory	Up to 16 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I MultiCard Reader 20-in-1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 1 x PCI-Express x4 (mech. x8) 2 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal, thereof 2 optional rear 1 x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 x Parallel (25pin with EPP and ECP) (optional) 1 x Ethernet (RJ-45) 1 x DVI (optional) 1 x DisplayPort (optional) 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Intel® 82567 LM
Dimensions (W x D x H)	203 x 390 x 392 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 85% / 87% / 85%
Special features	Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, up to 87 % energy efficient power supply, Blue Angel certified, Family Concept, Embedded Security (TPM)
Standard Warranty Duration**	3 years (depending on country)
Service level**	Bring-In / On-Site Service

Superior PCs
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO P7936 0-Watt
	The world's first 0-Watt PC
Operating system* preinstalled	Genuine Windows® 7 Home Basic 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts Mainboard	D3012 (µBTX)
Chipset	Intel® Q45
Processor Type, Second Level cache, Processor frequency	Intel® Core™2 Quad processor Q9650, 12 MB, 3.00 GHz Intel® Core™2 Quad processor Q9550, 12 MB, 2.83 GHz Intel® Core™2 Quad processor Q9505, 6 MB, 2.83 GHz Intel® Core™2 Quad processor Q8300, 4 MB, 2.50 GHz Intel® Core™2 Duo processor E8600, 6 MB, 3.33 GHz Intel® Core™2 Duo processor E8500, 6 MB, 3.16 GHz Intel® Core™2 Duo processor E8400, 6 MB, 3.00 GHz Intel® Core™2 Duo processor E7600, 3 MB, 3.06 GHz Intel® Core™2 Duo processor E7500, 3 MB, 2.93 GHz Intel® Pentium® processor E6600, 2 MB, 3.06 GHz Intel® Pentium® processor E5700, 2 MB, 3.00 GHz Intel® Celeron® processor E3400, 1 MB, 2.60 GHz
Memory	Up to 16 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I MultiCard Reader 20-in-1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 1 x PCI-Express x4 (mech. x8) 2 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal, thereof 2 optional rear 1 x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 x Parallel (25pin with EPP and ECP) (optional) 1 x Ethernet (RJ-45) 1 x DVI (optional) 1 x DisplayPort (optional) 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Intel® 82567 LM
Dimensions (W x D x H)	203 x 390 x 392 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 86% / 89% / 87%
Special features	0-Watt in off- / hibernating mode, Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, 89 % energy efficient power supply, Blue Angel certified, Switched monitor outlet, Family Concept, Embedded Security (TPM)
Standard Warranty Duration**	3 years (depending on country)
Service level**	Bring-In / On-Site Service (depending on country)

* Windows®XP Downgrade

Use of Microsoft® Windows® XP
End of October 2010 Microsoft stops the shipment of OEM Downgrade Media for Microsoft® Windows® XP **together** with a system.

1. Customers can still get the **Downgrade Medium for Microsoft® Windows® XP for Fujitsu client systems** pre-installed with one of the following operating systems:
   - Windows® 7 Professional
   - Windows® 7 Ultimate
   - Windows Vista® Business

   End users are allowed to order a Downgrade Medium for Microsoft® Windows® XP at extra costs until end of July 2011 if they have purchased a Fujitsu client system together with one of the OEM products listed above.
   For more information about ordering a Downgrade Medium for Microsoft® Windows® XP via Fujitsu Support please see:
   ts.fujitsu.com/support/xpdowngrade.html

2. **Use of Microsoft® Windows® XP Mode in combination with Windows® 7**
   Windows® 7 offers the possibility to run applications in Microsoft® Windows® XP Mode. This software can be downloaded from the Microsoft webpage free of charge:
   microsoft.com/windows/virtual-pc/download.aspx
   Following Microsoft products offer the possibility to run the Microsoft® Windows® XP Mode:
   - Windows® 7 Professional
   - Windows® 7 Enterprise
   - Windows® 7 Ultimate

3. **Pre-installation of Microsoft® Windows® XP via Fujitsu project support (Customizing Service)**
   Fujitsu offers a special support to ship systems with Microsoft® Windows® XP pre-installed at extra costs for customers with at least 25 ordered systems annually.
   To get further information please visit:
   ts.fujitsu.com/products/made4you/
   Recovery Media for Microsoft® Windows® XP are not shipped.
   If in addition a Downgrade Medium for Microsoft® Windows® XP is needed it has to be ordered separately via Fujitsu Support (see **1.**).

Order No.:
- Fujitsu Technology Solutions: A26361-K1007-Z172-1-7419, edition 1
- Fujitsu Ltd.: B5FH-D804-01DE-00

** Services

For today's business leaders and IT executives the question is not only what needs to be done, but how to do it quickly and effectively while still optimizing overall IT spending.

This is where Fujitsu can really help. We can provide you with a complete range of infrastructure services that allow you to deliver on this promise while reducing overall costs, improving ROI and still delivering outstanding service quality for your users.

Warranty comes standard with our products; it starts from the time of sale and is valid for a defined period of time. Minimum standard warranty is 12 months. The period and service level vary depending on product type and local regulations. Our ServicePack/Contract Hardware as part of Fujitsu's Maintenance and Support Services offering is the perfect extension on top of the standard warranty with various options of duration and of response or recovery time to fit customer needs and a flexible payment concept either up-front or on a regular basis.

For more information regarding Managed Services, Integration Services, Maintenance and Support Services or Financial Services please visit
ts.fujitsu.com/services

Expertise you can count on, wherever and whenever you need it.

The warranty can be claimed to the extent that the service concerned is available in the respective country. Please note that availability of all services cannot be guaranteed in all countries. The warranty agreed at the time of purchase may differ from the standard warranty stated here. In addition, as the customer you may have a right to legal claims not restricted by these warranty conditions.